

1258657

# THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office

*December 09, 2004*

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/520,868  
FILING DATE: *November 17, 2003*  
RELATED PCT APPLICATION NUMBER: *PCT/US04/38172*

Certified by



Jon W Dudas

Acting Under Secretary of Commerce  
for Intellectual Property  
and Acting Director of the U.S.  
Patent and Trademark Office

BEST AVAILABLE COPY

Please type a plus sign (+) inside this box →



PTO/SB/18 (5-03)

Approved for use through 04/30/2003. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

22154 U.S. PTO  
601520868

111703

INVENTOR(S)					
Given Name (first and middle (if any))		Family Name or Surname		Residence (City and either State or Foreign Country)	
Arndt Brent Christopher		Nottrott Sans		Toenisvorst, Germany Komoka, Ontario, Canada	
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
HYDROFORMING USING HIGH PRESSURE PULSATION DURING FLUID INTENSIFICATION CYCLE					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input checked="" type="checkbox"/> Customer Number		28886		Place Customer Number Bar Code Label here	
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name		Kevin S. MacKenzie			
Address		Clark Hill PLC			
Address		500 Woodward Ave., Suite 3500			
City		Detroit	State	MI	ZIP 48226-3435
Country		US	Telephone	(313)965-8331	Fax (313)965-8252
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification		Number of Pages 7		<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s)		Number of Sheets 1		<input type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees				FILING FEE AMOUNT (\$)	
<input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number		50-1759		\$160.00	
<input checked="" type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME Kevin S. MacKenzie

TELEPHONE (313)965-8331

Date

11/18/2003

REGISTRATION NO.

45,639

(if appropriate)

Docket Number:

20912-093632

### USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

P19LARGE/REV05

BEST AVAILABLE COPY

# **HYDROFORMING USING HIGH PRESSURE PULSATION DURING FLUID INTENSIFICATION CYCLE**

## **BACKGROUND OF THE INVENTION**

### **Field of the Invention**

The present invention relates to a method of hydroforming metal components, and more particularly to a method of hydroforming metal components using a high pressure fluid having a pulse applied to the fluid.

### **Description of the Related Art**

Hydroforming methods and processes are commonly known in the art for shaping tubular metal blanks, as well as, metal sheets. A typical hydroforming method used for shaping a tubular metal blank involves placing a tubular metal blank within a die cavity and introducing high pressure fluid within the interior of the blank causing the blank to expand outwardly to conform to the surface of the die cavity. Hydroforming metal parts has several advantages over typically used stamping operations to produce shaped metal components. Stamping operations typically involve pressing a metal part into a desired shape using a large hydraulic press to form the metal part. However, parts created using such a hydraulic press often have inconsistencies due to the characteristics of the forming operation. For example, metal parts formed using a stamping operation exhibit hardening of various portions of the part, usually at bend points or contours, resulting in material inconsistencies throughout the part. Also, metal parts having complex geometries cannot be produced in a single stamping operation due to inherent limitations in a stamping process. Therefore, welding and joining operations are often necessary to form a complex part, adding to the total cost of the part.

The process of hydroforming is capable of better repetition and precision when configuring complex shaped parts. As a result, complex parts can be formed in a single forming operation without the need for welding or joining processes which can lead to material distortions inherent in the joining processes.

Generally, hydroforming of sheet metal involves placing a sheet metal blank within a die wherein a pressurized fluid is introduced into the die cavity pressing the sheet metal against the contour of the die to form a shaped part.

While hydroforming produces parts having complex geometries using both tubular and sheet metal blanks, there are limitations to a hydroforming process including the thinning of base metal material of the blank during the forming process. Also, hydroformed parts may exhibit wrinkling or local deformations produced on the part during a forming process.

There is therefor a need in the art for a hydroforming process that limits the thinning of the base material of a blank, as well as improves the flow of material during the process resulting in a part having less material thickness variation over parts produced using conventional hydroforming processes.

## **SUMMARY OF THE INVENTION**

A method of hydroforming a metal part that includes the steps of: placing a part to be formed within a die, closing the die to enclose the part to be formed, introducing a high pressure fluid to an interior of the die for expanding the part against an interior surface of the die, the high pressure fluid having a pulse applied thereto for increasing a material flow of the part within the die during the hydroforming operation.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 shows schematically a preferred embodiment of a hydroforming device utilized by the method of the present invention.

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Referring to Figure 1, there is shown a preferred embodiment of a device 5 used in the method of hydroforming of the present invention. The hydroforming device 5 includes a variable frequency drive motor 10 connected through a bearing journal 15 to a connecting rod 20 attached to a piston plunger 25. The piston 25 is disposed within a cylinder 30 and is sealed within the cylinder 30 by an appropriate piston seal 35. The device 5 moves the cam operated piston 25 displacing fluid to create a frequency or pulse. The cylinder 30 is connected to a fluid line 40 that introduces the pressurized fluid into the forming die to create a formed metal part. The pulse or wave is generated by the variable frequency drive motor 10 connected to the cam operated piston 25.

In a preferred aspect of the present invention, the variable frequency drive motor 10 has a frequency range of from 5 to 60 hertz. The frequency range of from 5 to 60 hertz results in a frequency fluid volume displacement in the range of from .001 to 5 liters of water. The piston 25 amplitude preferably has a range of from 1 to 50 mm resulting in a pressure amplitude in the range of from 5 to 500 bar. The frequency pressure range preferably, is from 5 to 1500 bar with a frequency duration of preferably 30 seconds. Through put speeds for parts formed by the hydroforming operation preferably are in the range of from 5 to 60 seconds.

As noted above, tubular structures as well as sheet materials may be utilized as blank materials for the hydroforming operation of the present invention.

While a preferred device is shown in Figure 1 for introducing the pulse into the hydroforming fluid, other methods or devices may be utilized by the present invention. For example, valves associated with the fluid line 40 leading to the forming die used in the hydroforming operation can be manipulated or oscillated; thereby introducing a frequency or pulse to the hydroforming fluid, preferably in the range of the characteristics outlined above with respect to the preferred embodiment.

The method of the present invention includes placing a part to be formed within a hydroforming die, closing the die, and then introducing a high pressure fluid to an interior of the die, the high pressure fluid having a pulse applied thereto. The high pressure fluid expands the part against an interior surface of the die resulting in a formed metal part. As the high pressure fluid is introduced to the die generally, the metal part begins expanding against the die surface. Generally in a conventional hydroforming operation, a static pressure of from 300 to 500 bar is utilized to expand the metal against the die surface. The conventional hydroforming operation or method, as stated above uses a constant or static pressure resulting in a constant expansion of the metal against the surface of a die.

The method of the present invention utilizes a wave or pulse flow of pressure; thereby increasing the material flow in the cavity or die by not constantly expanding the metal blank, resulting in a more consistent wall thickness, especially in portions of a part having a complex curvature that would often see thinning when a constant pressure hydroforming fluid is applied to the die.

Many modification and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims, the invention may be practiced other than as specifically described.

What is claimed is:

1. A method of hydroforming a metal part comprising the steps of:  
placing a part to be formed within a die;  
closing the die to enclose the part to be formed;  
introducing a high pressure fluid to an interior of the die for expanding the part against an interior surface of the die, the high pressure fluid having a pulse applied thereto for increasing a material flow of the part within the die.



## **ABSTRACT**

A method of hydroforming a metal part. The part is placed within a die. The die is closed and a high pressure fluid is introduced to an interior of the die for expanding the part against an interior surface of the die. The high pressure fluid has a pulse applied thereto for increasing a material flow of the part within the die during the hydroforming operation.




FIGURE 1

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/038172

International filing date: 15 November 2004 (15.11.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US  
Number: 60/520,868  
Filing date: 17 November 2003 (17.11.2003)

Date of receipt at the International Bureau: 20 December 2004 (20.12.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse